

AS Serie



Technische Daten:	AS 10/2	AS 10/2	AS 15/2
Cabinet	Passive	Passive	Passive
Impedance	8 Ω	8 Ω	8 Ω
Rated Power RMS	300 Watt	350 Watt	400 Watt
Program Power	600 Watt	700 Watt	800 Watt
SPL 1W/1m	98 dB	98 dB	99 dB
Max. SPL	125 dB	125 dB	127 dB
Frequency response	55 Hz - 20 kHz	50 Hz - 20 kHz	50 Hz - 20 kHz
Coverage angle	100° x 50° turnable	100° x 50° turnable	100° x 50° turnable
Crossover frequency	2,7 kHz	2,7 kHz	2,7 kHz
Components High	1,35" diaph. driver	1,75" diaph. driver	1,75" diaph. driver
Components Low (Mid)	10" Woofer 2" voice coil	12" Woofer 3" voice coil	15" Woofer 3" voice coil
Protection	PTC driver protection	PTC driver protection	PTC driver protection
Material	Multiplex	Multiplex	Multiplex
Finish	black lacquer	black lacquer	black lacquer
Handle	1	1	2
Flange	1	1	1
Flying points	7 / M8	7 / M8	7 / M8
Dimensions mm (W x H x D)	320 x 530 x 310	380 x 600 x 350	460 x 690 x 400
Weight (kg)	13 kg	17 kg	22 kg

Keine Haftung für technische Änderungen oder Irrtum, Abbildung ähnlich, Änderungen vorbehalten.