

SB 15 Sub



| Technische Daten: | SB 15 N |
|---------------------------|-----------------------------|
| Cabinet | Passive |
| Impedance | 8 Ω |
| Rated Power RMS | 500 Watt |
| Program Power | 1000 Watt |
| SPL 1W/1m | 99 dB |
| Max. SPL | 126 dB |
| Frequency response | 45 Hz - 120 Hz |
| Components Low | 15" Woofer 3" voice coil |
| Material | Multiplex |
| Finish | black lacquer |
| Handle | 2 |
| Flange | M 20 |
| Dimensions mm (W x H x D) | 450 x 650 x 540 |
| Weight (kg) | 32 kg |

| Technische Daten: | SB 15 A |
|---------------------------|--------------------------------|
| Cabinet | Active |
| Power | 500 / 1000 W |
| Amping | digital amp |
| Frequency response | 45 Hz - 120 Hz |
| Components Low | 15" aa CRAAFT 3" voice coil |
| Crossover frequency | 120 Hz |
| Protection | Limiter |
| Material | Multiplex |
| Finish | black lacquer |
| Handle | 2 |
| Flange | M 20 |
| Dimensions mm (W x H x D) | 420 x 540 x 550 |
| Weight (kg) | 28,5 kg |

Keine Haftung für technische Änderungen oder Irrtum, Abbildung ähnlich, Änderungen vorbehalten.